

DESCRIPTION

A versatile quick drying, single pack anti-corrosive primer for steel. Suitable for use under a wide variety of conventional finishes, combining excellent adhesion and ease of application. Makes an ideal primer for overcoating with Johnstone's Semi-Gloss Steel & Cladding Topcoat.

RECOMMENDED USES

An anti-corrosive primer for ferrous metals and all suitably prepared non-ferrous substrates.

SPECIAL PROPERTIES

Excellent anti-corrosive properties on properly prepared steel.

COLOUR RANGE

Red Oxide; Grey; White.

FINISH

Matt.

VOLUME SOLID

34%

COVERAGE

Johnstone's Quick Dry Zinc Phosphate Primer will cover at the rate of approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Recoat after 16-24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

TC2 Thinner and Cleaner.

VOC CONTENT

HIGH VOC CONTENT 25–50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010).
This product contains max 450g/l VOC.

FILM THICKNESS

Wet: 75µm, dry: 35µm.

SIZE

2.5 Litre and 5 Litre (White available in 5 Litre only).

PREPARATION

STEEL: Blast cleaned to SIS-Sa 2^{1/2} minimum or mechanically prepared to SIS-St 3 minimum. Previous suitable coats should be clean, dry and abraded if necessary. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

APPLICATION

Stir thoroughly before use. Easy to apply by brush.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC2 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Toxic to aquatic life with long lasting effects.
- Avoid release to the environment.
- Collect spillage
- Contains 2-butanone oxime. May produce an allergic reaction.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.