

Anti-Corrosive Metal Primer

Leyland Trade Anti-Corrosive Metal Primer is suitable for use on all metal surfaces. Its anti-corrosive properties make it ideal for helping prevent rust.

Recommended uses

*Interior ✓ Exterior ✓

Type of substrate

All types of metal including ferrous metals and all suitably prepared non-ferrous metal.

Colour availability

Grey and Red Oxide (2.5ltr)

Finish

Matt

Volume solid

34%

Coverage

1 litre will cover approximately 1 square metres, depending on the nature and porosity of the surface.

Drying time

Recoat after 14-16 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

VOC content

HIGH VOC CONTENT 25-50% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500 g/l (2010). This product contains max 450 g/l VOC.

Film thickness

Wet: 75µm

Dry: 35µm

Preparation

All surfaces to be painted should be clean, dry and free from loose or flaking material. Existing rust or millscale should be removed from iron and steel. Loose or defective paint should be removed, stripping to the bare surface if necessary. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

Application

Stir thoroughly before use. Apply by brush or roller. To ensure the best results the brush should be fully loaded. Do not thin.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Flammable liquid and vapour.
- Toxic to aquatic life with long lasting effects.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Avoid release to the environment. Collect spillage.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- *Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

