



PAIN T PANTHER PAINT & VARNISH REMOVER

- A highly effective varnish remover and paint stripper
- Suitable for use on water, oil and solvent-based paints, varnishes and lacquers
 - For both interior and exterior use
 - Removes up to 6 layers of paint in 5 minutes
- Non-drip gel formula ideal for vertical or awkward areas
 - Methylene chloride free

For decorative plaster coving, cornicing and ceiling roses, carved or shaped wood, decorative metal fireplaces and other surfaces with a decorative design, that has been in-filled with paint, consider [PeelAway 1 Paint Remover](#) and [PeelAway 7 Paint Remover](#). Also available in a handy [PeelAway 1 and 7 Sample Twin Pack](#).

Surface Preparation

Areas to be stripped should be cleaned to remove any surface dirt and debris that may restrict contact with *Paint Panther Paint and Varnish Remover*. Ensure that any surfaces not intended to be stripped are covered and protected from this product.

Paint Panther gel contains corrosive substances and should only be used in a well ventilated area with protective clothing such as gloves, safety glasses or goggles.

Application

Always do a test area to assess performance and compatibility before starting any project. Follow the manufacturer's instructions on the tin at all times. Refer to msds.

1. Using a suitable brush, paint a thick coat of Barretine Paint Panther onto about a square meter at a time
2. Wait between 5 and 10 minutes before removing the gel
3. Remove the wood stripping gel and stripped product with a scraper (recommended) or steel wool (wearing protective gloves)
4. Light scoring of the coated surface may enhance performance, however do not sand if any coats contain lead
5. When finished, follow with a wash of white spirit

If required, the process can be repeated again for stubborn areas or where there are many layers of paint.

Technical Information

Number of coats	1-2
Theoretical Coverage	3 sq.m/litre
Drying Time	15 minutes