

DESCRIPTION

A water based solution formulated for the treatment and control of mould, fungal and algal growth prior to painting.

RECOMMENDED USES

For interior and exterior treatment of walls, ceilings and masonry including plaster, concrete, cement render, brick and stone.

SPECIAL PROPERTIES

Control of mould and algal growth.

COLOUR RANGE

Clear.

FINISH

Not applicable.

VOLUME SOLID

Not applicable.

COVERAGE

Johnstone's Sterilisation Wash will treat approximately 3-7 square metres per litre after dilution, depending on the degree of algal growth.

DRYING TIME

Allow 24 hours drying between treatments or before overpainting.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

Not applicable.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

PREPARATION

Remove all loose and flaking material and any heavy growth, moss etc, with a stiff brush.

SIZE

2.5 Litre

APPLICATION

Stir thoroughly before use. Dilute 1 part product to 4 parts clean water. Apply by brush working well into the affected areas. Allow to dry for 24 hours before washing/brushing off to remove all loose and flaking material. A second application should be carried out before painting is undertaken.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS**Statutory conditions relating to use**

- FOR USE ONLY AS A SURFACE BIOCIDES.
- FOR USE ONLY BY PROFESSIONAL OPERATORS.
- DILUTE 1 PART PRODUCT WITH 4 PARTS WATER THEN APPLY AT A RATE OF 1 LITRE OF DILUTED PRODUCT PER 3-7 SQUARE METRES OF SURFACE BY BRUSH.
- The (COSHH) Control of Substances Hazardous to Health Regulations 2002 may apply to the use of this product at work.
- Engineering control of operator exposure must be used where reasonably practicable in addition to the following items of personal protective equipment.
- Wear suitable protective clothing, gloves and eye/face protection.
- AVOID EXCESSIVE CONTAMINATION OF COVERALLS AND LAUNDER REGULARLY. However, engineering controls may replace personal protective equipment if a COSHH assessment shows they provide an equal or higher standard of protection.
- When using do not eat, drink or smoke.
- DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.
- COVER WATER STORAGE TANKS BEFORE APPLICATION.
- This material and its container must be disposed of in a safe way.
- AVOID ALL CONTACT WITH PLANT LIFE.
- ENSURE THERE IS A PHYSICAL BARRIER TO PREVENT CONTACT BY UNPROTECTED PERSONS AND ANIMALS UNTIL TREATED SURFACES ARE DRY.
- **Read all precautions before use (HSE No. 7359).**
- Wash any contamination from skin and eyes immediately.
- Wash hands and exposed skin before meals and after use.
- Keep away from food, drink and animal feeding stuffs.
- Keep in original container tightly closed in a safe place.
- Keep out of the reach of children.
- **CONTAINS: BENZALKONIUM CHLORIDE 5.0% W/W (50g/l).**
- This product is approved under The Control of Pesticides Regulations 1986 for use as directed (HSE No.7359).