

## DESCRIPTION

Johnstone's Acrylic Durable Matt is a premium quality emulsion formulated for interior use on walls and ceilings. In addition it can be used on suitably primed woodwork and radiators. This low odour paint is washable and wipeable, providing a tough finish that is resistant to condensation, yellowing and most household stains. Its outstanding durability makes it ideal for use in kitchens, bathrooms, hotels, hospitals and public buildings.

## RECOMMENDED USES



Suitable for interior use.

## TYPE OF SUBSTRATE

Interior walls and ceilings. Suitably primed woodwork and radiators.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

33.6%

## COVERAGE



Approximately 11–13 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Low VOC content 0.3–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).  
This product contains max 30g/l VOC.

## FILM THICKNESS

Wet: 83µm, dry: 28µm.

## KEY PROPERTIES

- Highly durable and washable.
- Resists stains.
- Retains a true matt finish.
- Meets Class 1 of ISO 11998 for scrub resistance.

## PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any crazed or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Joncyl Water Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Acrylic Matt. Prime bare timber and metal surfaces with an appropriate Johnstone's primer. Allow radiators to cool before painting. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

## APPLICATION



Stir well before use and apply by brush, roller or paint pad. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure the roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading. Also suitable for application by spray. Do not apply when air or surface temperature is less than 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and octhilonone (ISO). May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.

## SIZES

2.5 Litre, 5 Litre and 10 Litre\*

\* 10L available in BW and Magnolia only