



# Flame Retardant Intumescent Upgrade System - Acrylic Eggshell

## DESCRIPTION

Johnstone's Flame Retardant Intumescent Upgrade System Acrylic Eggshell is a high quality hard wearing product for use as part of the Johnstone's Flame Retardant Intumescent Upgrade System. A system which successfully upgrades a Class 4 'Blue Board' substrate to Class 0, protecting against the spread of flame. This product should only be used as part of a written specification by PPG Architectural Coatings UK Limited.

## RECOMMENDED USES



For use on internal linings, broad wall and ceilings.

## COLOUR RANGE

Available in 7,000 colours (pastel colours only).

## FINISH

Eggshell.

## VOLUME SOLID

45%

## COVERAGE



Johnstone's Flame Retardant Intumescent Upgrade System Acrylic Eggshell should cover 12\* square metres per litre. \*This coverage should not be exceeded as it complies with the Johnstone's Class 0 Flame System fire testing report.

## DRYING TIME



Recoat after 4 hours minimum and a maximum of 7 days.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

## THINNER

Water.

## VOC CONTENT

LOW VOC CONTENT 0.30-7.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/1): 140g/l (2010).

This product contains max 15g/l VOC.

## FILM THICKNESS

Wet: 83µm, dry: 33µm.

## SIZE

5 Litre

## PREPARATION

Surfaces must be sound, clean, dry and free from all loose and flaking materials and surface contaminants. Surfaces should be prepared in accordance to the written specification provided by PPG ACUK&I Ltd. For advice, please contact the PPG Extra Technical Team on 01924 354354.

## APPLICATION



Stir thoroughly before use. Apply two coats by brush or medium pile roller. Ensure good ventilation during application and drying. Do not apply in temperatures below 10°C or in damp conditions.

## CLEANING



Replace lid firmly after use. Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with clean water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. To avoid the risk of spillage, always store and transport in a secure upright position.

## PRECAUTIONS

### PAINT PRODUCT

Use only in well ventilated areas.

Avoid contact with skin and eyes.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Keep out of the reach of children.

This material and its container must be disposed of in a safe way.

Safety data sheet available for professional user on request.



For information, advice or Specifications for the Johnstone's Flame Retardants range, please contact the PPG Extra team on 01924 354354.



PAINT TO BE PROUD OF

For further information and advice please call 01924 354000  
Find out more at: [www.johnstonestrade.com](http://www.johnstonestrade.com)