

DESCRIPTION

Johnstone's Quick Dry Woodfiller is a ready to use wood filler designed to work on all exterior and interior wood substrates. The paste restores wood with small slits, dents and cracks. This fast drying filler does not crack and can be over coated with paint, varnish or stain.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Ideal for interior and exterior wood and timbers.

COLOUR RANGE

White.

FINISH

N/A.

VOLUME SOLID

N/A.

COVERAGE

Variable depending on application method, the surface condition and the depth of the area being filled.

DRYING TIME*



Touch dry 30 mins, recoatable 3 hours under normal drying conditions. Do not apply in temperatures below 10°C.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

Clean Water.

VOC CONTENT

N/A

FILM THICKNESS

N/A

KEY PROPERTIES

- Ready to use paste for minor repairs and cracks
- Contains wood fibres for a natural appearance
- Solid and durable

PREPARATION

Before applying Johnstone's Quick Dry Woodfiller ensure that all timber to be treated is sound, dry and free from dust, grease or any other surface contaminants. Sand smooth natural planed wood and wipe clean with White Spirit to remove any natural oils or resins and allow to dry. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir Johnstone's Quick Dry Woodfiller thoroughly before and during use. Tin includes stirring space. Apply and smooth the paste until even with spatula. After drying, sand level with substrate. Brush away dust and overcoat with paint, varnish or stain.

CLEANING



Clean tools with clean water. Unopened Johnstone's Quick Dry Woodfiller can last up to 24 months, this will be significantly reduced upon opening.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- Wash hands thoroughly after handling.

SIZE

450g.