

DESCRIPTION

Johnstone's Quick Dry Matt Blackboard Paint gives an attractive smooth, non reflective black finish formulated for interior use on wood and metal. Suitable for use on beams, panelling, doors, decorative ironwork, stage scenery, darkrooms and blackboards.

RECOMMENDED USES



Beams, panelling, doors, decorative ironwork, stage scenery, darkrooms and blackboards.

SPECIAL PROPERTIES

Non-reflective, washable.

COLOUR RANGE

Black.


FINISH

Matt.

VOLUME SOLID

52%.

COVERAGE



Johnstone's Quick Dry Matt Blackboard Paint will cover at the rate of approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 2–4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Water

VOC CONTENT

LOW VOC CONTENT 0.3-7.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010).
This product contains max 20g/l VOC.

FILM THICKNESS

Wet: 50µm, dry: 25µm.

SIZE

1 Litre and 2.5 Litre.

PREPARATION

All surfaces to be painted should be sound, clean, dry and free from loose and flaking material. Previously painted surfaces should be rubbed down with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Prime bare surfaces with the appropriate Johnstone's Primer. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

APPLICATION



Stir well. Easy to apply by brush, roller or paint pad.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and octhiline (ISO). May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.