



# **VANDAL GUARD**

## **PERMANENT CLEAR EXTERNAL COATING**

### **DESCRIPTION & USE:**

A clear, colourless, weather-resistant coating which stops the adhesion of fly posters and all types of graffiti to bare or painted brick, stone, concrete, render, timber and metal, yet allows moisture to escape. Suitable for internal and external use.

### **APPEARANCE:**

Clear and colourless matt, almost undetectable on most surfaces. A gloss finish is also available. There is the possibility of slight darkening to pale, porous surfaces such as natural stone. Although very seldom an issue, Thermoguard Dark-Resisting Sealer can help overcome it (a small test area is recommended) - Available as part of a coloured paint system where required.

### **GRAFFITI & POSTER REMOVAL:**

Commonly used poster adhesives will simply not adhere to the surface, so posters fall off of their own accord or with a gentle tug.

Graffiti is simply removed from smooth surfaces with warm soapy water and a sponge and from rough surfaces with a soft bristle brush or warm water pressure wash.

There is no need to use dangerous chemical removers.

### **LIFE EXPECTANCY:**

Seven years, after when a further single coat of Thermoguard Vandal & Poster Guard should simply be applied.

### **RAPID PROTECTION & EASY TO APPLY:**

Thermoguard Vandal & Poster Guard is rapid-drying and re-coating enabling the full system to be applied and full protection against graffiti and posters be achieved all on the same day.

Both Thermoguard Vandal & Poster Guard and Thermoguard Dark-Resisting Sealer are easy to apply, single pack products.

### **APPLICATION:**

- Ensure surface is clean, sound and dry.
- Abrade any hard and non-porous surface to provide a key.
- Apply 2 coats Thermoguard Vandal & Poster Guard at 10sq. metres per litre (5sq. metres per litre on rough surfaces or for the first coat on porous surfaces )
- Allow each coat to dry before applying subsequent coat (2 hours in good conditions) (To pale, porous brick or natural stone surfaces where a test has revealed darkening any slight darkening effect can be reduced by applying :- 1 coat Thermoguard Dark-Resisting Sealer prior to VandalGuard - We recommend a small test area prior to application.
- Application by roller, brush or airless spray with 15-17thou tip.
- Min. temperature during application 5C, surface temperature min 3C above dew point, max humidity 85%.
- Apply in dry weather.

Thermoguard Ltd

Technical Tel. 01624 825115 Fax. 01624 825526 Email [sales@thermoguard.co.uk](mailto:sales@thermoguard.co.uk)