



**Paints Limited**

[www.kenyonpaints.co.uk](http://www.kenyonpaints.co.uk)

---

**FOR SALES & TECHNICAL SUPPORT**

Call **0161 665 4470** Fax **0161 627 5072**

Email [sales@kenyonpaints.co.uk](mailto:sales@kenyonpaints.co.uk)

Kenyon Paints Limited Regent Street Oldham OL1 3TZ

---

**Product Name:** MOLOCHITE

**Reference Number:** -

**Coating Type:** Inert china clay aggregate.

**Typical Uses:** As a non-skid aggregate for use with the Dacrylate range of floor paints.

### Instructions for Use:

**Method One:** Whilst the final coat of floor paint is still wet, sprinkle the 'Molochite' evenly over surface.

**Spread Rate for Molochite:**

1-1½ kg per 40m<sup>2</sup> depending on degree of 'non-skid' required.

**Method Two:** Immediately prior to application of the final coat of floor paint, thoroughly mix into the paint, 1 kg of Molochite.

**NB:** The paint/Molochite mix should be stirred at intervals during application to prevent settling of Molochite additive.

**Note:** The roughness or texture of the non-skid surface can be reduced if necessary by the application of a further thin coat of the floor paint.

**Health & Safety:** Please refer to relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

**Issued:** November 2001 SW/DAE/CR