



**Paints Limited**

[www.kenyonpaints.co.uk](http://www.kenyonpaints.co.uk)

---

**FOR SALES & TECHNICAL SUPPORT**

Call **0161 665 4470** Fax **0161 627 5072**

Email [sales@kenyonpaints.co.uk](mailto:sales@kenyonpaints.co.uk)

Kenyon Paints Limited Regent Street Oldham OL1 3TZ

---

## PRODUCT INFORMATION

- Product Name** : **Clear Fungicidal Masonry Sealer**
- Reference Number** : 150-50
- Coating Type** : Water-based modified acrylic with fungicidal additive for use with water-based coating systems.
- Typical Uses** : Penetrating sealer for porous substrates, aged friable masonry paints, new concrete, rendering, brick, plaster, etc. Designed to be overcoated by 'solid' coloured topcoat paint systems.
- Colours Available** : Clear finish only (*also available with White 'Tracer' see 150-429*).
- Application Rate** : **Low porosity** (ie. old emulsion paint) : Approx. 8-10m<sup>2</sup> per litre  
**High porosity** (ie. new brick concrete) : Approx. 4-6m<sup>2</sup> per litre
- Drying Time at 20°C** : **Touch Dry** : 30 minutes  
(*will vary with temperature, air movement, etc.*) **Firm Dry** : 2 hours  
**Overcoat** : 2 hours
- Note** : *Drying times will vary depending on humidity, air circulation, ventilation, etc.*
- Packaging** : 2.5 litre containers and 5 litre containers.
- Shelf Life** : 2 years in unopened containers when stored under cover in good storage conditions.
- Storage** : Under cover within a temperature range of 5°C to 32°C
- Surface Preparation** : Remove all loose flaking paint, friable material, etc., by scraping, wire brushing, etc., to leave sound surfaces. Wash down with detergent water followed by clean water rinse. Allow to dry.
- Areas susceptible to fungal growth should be scraped clean and treated with 20% domestic bleach solution followed by clean water rinse.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

- Application** : Apply liberally by brush. Brush well into textured surfaces, mortar courses, etc. May be applied by spray to large areas.
- Note** : *Clear Fungicidal Masonry Sealer should **NOT** be applied in wet, damp conditions or if rain is threatened. Relative humidity should be **less than 85%**. Ambient temperature should be above 5°C until coating has fully dried.*
- Clean-up** : Clean water.
- Limitations** : For cosmetic reasons, Dacrylate Clear Fungicidal Masonry Sealer is **NOT** suitable as a clear topcoat in its own right.
- Health and Safety** : Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.