



Paints Limited

www.kenyonpaints.co.uk

FOR SALES & TECHNICAL SUPPORT

Call **0161 665 4470** Fax **0161 627 5072**

Email sales@kenyonpaints.co.uk

Kenyon Paints Limited Regent Street Oldham OL1 3TZ

Product Name:	WAYMARK LINE MARKING PAINT
Reference Number:	150-Line
Coating Type:	Spirit based hard resin.
Typical Uses:	Fast-drying lining paints for use on concrete and asphalt floors. Non-bleeding on bitumen/asphalt floors.
Colours Available:	Yellow - Ref:150-58 White - Ref:150-59
Appearance of Dried Film:	Matt.
Volume Solids:	50%.
Dry Film Thickness:	Typical: 50 microns.
Theoretical Coverage:	10m ² per litre at 50 microns dry film thickness (equivalent to a line 100 metres and 100 mm wide).
Drying Time at 20°C: (Will vary with temperature, air movement etc.)	Touch Dry: 10 minutes. Firm Dry: 30 minutes. Overcoat: After 1 hour.
Packaging:	5 litre, 2½ litre and 1 litre containers.
Shelf Life:	6 months in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.
Surface Preparation:	Remove all dirt, dust, grease etc., by washing with dilute detergent water followed by clean water rinse. Allow to dry <u>completely</u> .
Application:	Ensure surface is clean and dry. Apply by brush, roller or special line-marking equipment.
Clean Up:	Dacrylate Thinner R19.
Health and Safety:	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: November 2001

SW/DAE/CR