

## All Purpose Primer

All Purpose Primer is ideal when priming is required on a number of different surfaces. It has been formulated as a general purpose primer to provide a resilient film and to promote adhesion on most surfaces both inside and out.

### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Wood, Metal, Plaster, Masonry.

### Colour availability

White (2.5ltr and 750ml)

### Finish

N/A

### Volume solid

61%

### Coverage

1 litre will cover approximately 12 square metres, depending on the nature and porosity of the surface.

### Drying time

Touch dry in 4-6 hours.  
Recoat after 16-24 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

### VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300 g/l (2010). This product contains max 300 g/l VOC.

### Film thickness

Wet: 85µm  
Dry: 52µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down sound previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### Application

Stir well before use. Apply liberally, brushing firmly onto the surface. One coat is normally sufficient on most surfaces.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

### Warning

- Flammable liquid and vapour.
- Contains 2-butanone oxime.  
May produce an allergic reaction.
- Safety data sheet available on request.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

