

Anti-Slip Floor Paint

A semi-gloss coating that includes a light aggregate that gives slip resistant properties. It is suitable for use on internal concrete, steel and wooden floors in light to medium traffic areas and can also be used outside to highlight walkways, car park spaces and other markings but is not suitable for use on large external areas.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Concrete, steel and wooden floors. For further information on substrates please contact Technical Advisory on 01924 354354.

Colour availability

Slate and Tile Red (5ltr)

Finish

Semi-gloss

Volume solid

48%

Coverage

1 litre will cover approximately 11 square metres per litre, depending on the nature and porosity of the surface. When using more than one tin of a colour in the same area, intermix before use.

Drying time

Recoat after 16-24 hours

Transportation and storage

STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 8 kilograms.

VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 500g/l VOC.

Film thickness

Wet: 90 micron

Dry: 40 micron

Preparation

All surfaces to be painted should be clean, dry and free from loose or flaking material. New concrete or cement should be allowed to mature for several months before painting. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood

and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

Application

Stir well before use. Apply by brush or roller which should be fully loaded for best results. Apply paint evenly by brush and avoid overspreading. Recoat after 16-24 hours. The coating is fully cured in 7 days.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- **Flammable liquid and vapour.**
- Contains 2-butanone oxime.
May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

