

Brushable Bitumen

A corrosion resisting, waterproofing paint formulated for exterior use on a variety of surfaces including metal, stone and concrete. The finish provided is also resistant to dilute acids and alkalis.

Recommended uses

Exterior ✓

Type of substrate

Metal, concrete, stone. For further information on substrates please contact Technical Advisory on 01924 354354.

Colour availability

Black (5ltr)

Finish

Mid sheen

Volume solid

47%

Coverage

1 litre will cover approximately 8 square metres depending on the nature and porosity of the surface being painted.

Drying time

Allow 24 hours between coats.

Transportation and storage

STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 8 kilograms. Store in a well-ventilated place.

Keep cool. Store locked up.

VOC content

HIGH VOC CONTENT 25 - 50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010).

This product contains max 500g/l VOC.

Film thickness

Wet: 85µm Dry: 40µm

Preparation

All surfaces to be painted should be clean, dry and free from loose and flaking material. Any rust should be removed by wire brushing. Wear a suitable face mask when creating dust. Prime bare surfaces with an appropriate Primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

For further advice contact Technical Advisory on 01924 354354.

Application

Apply a minimum of 2 coats by brush or roller. Do not apply over tar based products or surfaces that can rise above 65°C. Do not overcoat with other solvent based paints as bleeding may occur. Allow 24 hours between coats.

Take all the necessary precautions when working at height.

Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. Do not overcoat with other solvent based paints as bleeding may occur.

Danger

• Flammable liquid and vapour.

- Vapours may cause drowsiness and dizziness.
- Toxic to aquatic life with long lasting effects.
- Causes damage to the central nervous system through prolonged or repeated exposure.
- Hazardous ingredients: Solvent Naphtha (petroleum), medium aliphatic.
- Safety data sheet available on request.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Avoid release to the environment.
- Collect spillage.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
- Do not breathe vapours.
- Wear protective gloves, eye or face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Store locked up.

