

## Exterior Water Seal

A clear waterproofing treatment that contains effective moisture resisting technology to protect porous walls against moisture and water infiltration. The water repellent but breathable barrier protects against rain, damp and frost allowing it to also help prevent dirt build-up. Particularly recommended for use on brick, cladding materials, soft stone, coated cement and plaster.

### Recommended uses

Exterior ✓

### Type of substrate

All porous substrates: Brick, cement, stone tile. For further information on substrates please contact Technical Advisory on 01924 354354.

### Colour availability

Clear (5ltr)

### Finish

Clear

### Volume solid

N/A

### Coverage

1 litre will cover approximately 4 to 6 square metres depending on the nature and porosity of the surface being treated.

### Drying time

Touch dry in approximately 30 minutes and completely dry in 6 hours. Drying time on some surfaces during winter may be longer.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 8 kilograms.

### VOC content

N/A

### Film thickness

N/A

### Preparation

Leyland Truguard Exterior Water Seal can only be used on porous substrates. It is recommended that you carry out a test beforehand on a small area. Depending on the nature and porosity of the substrate it is possible for this product to slightly change the appearance of the treated area.

Ensure the surface is clean and free from grease. Remove all loose and flaking material then brush, scrape and remove dust from the surface. Remove any moss, algae or mould with an appropriate fungicidal wash. Let the area dry for a minimum of 2 hours. Examine all surfaces prior to application in order to determine the nature of the preparation required.

For further advice contact Technical Advisory on 01924 354354.

### Application

Mix well before use and apply evenly by brush, roller or spray. When spraying do not dilute. Do not use in temperatures below 5°C or above 35°C or when rain or freezing weather is imminent. Apply a single coat, starting at the bottom and working to the top until the substrate is saturated.

**Take all the necessary precautions when working at height.**

### Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### Warning

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.