

Stabilising Damp Treatment

A dual purpose clear stabilising solution and pre-treatment for interior and exterior damp or wet walls ideal for use before painting or wallpapering. The protective, waterproofing treatment helps keep the surface dry and makes it more suitable for over coating. The treatment will also prevent the formation of unsightly white salt deposits known as efflorescence or saltpeter.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Plaster, plasterboard, gypsum. For further information on substrates please contact Technical Advisory on 01924 354354.

Colour availability

Clear (750ml & 2.5ltr)

Finish

Clear

Volume solid

N/A

Coverage

1 litre will cover approximately 4 to 6 square metres depending on the nature and porosity of the surface being treated.

Drying time

Touch dry in approximately 2 hours and completely dry in 6 hours. Drying time on some surfaces during winter may be longer.

Transportation and storage

PROTECT FROM FROST

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 4 kilograms. (2.5L only)

Do not use empty container for storing food.

VOC content

N/A

Film thickness

N/A

Preparation

The surface to be treated must be clean and free from grease. Do not use over existing paintwork. Remove all loose and defective paint. Brush, scrape and/or remove dust from the surface. Remove any moss, algae or mould with an appropriate fungicidal wash. If the treated area has been very wet, allow a period of one month before covering with paint or wallpaper. Ensure that the substrate is porous. For optimum results, treat any structural

causes of moisture first. Avoid contact with plants, flowers or grass and protect glass before treatment. It is strongly recommended that you carry out a test beforehand on a small area. Depending on the nature of the substrate it is possible for this product to leave a satin finish or darken the area. Although this product is used to treat damp areas it does not replace the need to repair any structural faults or cracks that allow damp to penetrate into the fabric of the walls.

For further advice contact Technical Advisory on 01924 354354.

Application

Stir well before use and apply well by brush or roller. Apply a single coat, starting at the bottom, working to the top until the substrate is saturated. Do not use in temperatures below 5°C or above 35°C or when rain or freezing weather is imminent.

Take all the necessary precautions when working at height.

Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Danger

• Causes severe skin burns and eye damage.

• Hazardous ingredients: Potassium methylsilanetriolate.

• Safety data sheet available on request.

• If medical advice is needed, have product container or label at hand.

• Keep out of reach of children.

• Wear protective gloves, protective clothing, eye/face protection.

• Wash exposed skin thoroughly after handling.

• IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

• IF ON SKIN: Remove immediately all contaminated clothing. Rinse with water/shower.

• IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

• Dispose of contents/container to a waste disposal site in accordance with local/national regulations.

• Store locked up.

